

Description

Fastener Length: 1-53/64", Thread: 1/4-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NR5K19
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-580-6464
Schedule B:	8108.90.3060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N BACB30NR5K19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.449 Inches Minimum And 0.459 Inches Maximum
Fastener Length:	1.783 Inches Minimum And 1.828 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.310 Inches Minimum And 0.312 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms10-85, Type 1, Class A Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NR5K19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.