

**Description**

Fastener Length: 1-3/16", Thread: 1/4-24, Thread Length: 29/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | BACB30NR5K9      |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5306-01-580-6491 |
| Schedule B:        | 8108.90.3060     |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N BACB30NR5K9 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.449 Inches Minimum And 0.459 Inches Maximum  |
| <b>Fastener Length:</b>                               | 1.157 Inches Minimum And 1.202 Inches Maximum  |
| <b>Head Style:</b>                                    | Dished Hexagon   |
| <b>Head Height:</b>                                   | 0.156 Inches Minimum And 0.171 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.492 Inches Minimum And 0.502 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.310 Inches Minimum And 0.312 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches   |
| <b>Grip Length:</b>                                   | 0.552 Inches Minimum And 0.572 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Minimum Tensile Strength:</b>                      | 95000 Pounds Per Square Inch   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Surface Finish:</b>                                | 63.0 Microinches Bearing Surface Of Head   |
| <b>Material:</b>                                      | Titanium Alloy Overall   |
| <b>Material Document And Classification:</b>          | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Aluminum Overall   |
| <b>Surface Treatment Document And Classification:</b> | Bms10-85, Type 1, Class A Assn Std Single Treatment Response Overall                                     |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NR5K9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.