

P/N BACB30NR6K14

Description

Fastener Length: 1-9/16", Thread: 3/8-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	BACB30NR6K14
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-580-6496
Schedule B:	8108.90.3060
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N BACB30NR6K14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.465 Inches Minimum And 0.475 Inches Maximum
Fastener Length:	1.518 Inches Minimum And 1.563 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.373 Inches Minimum And 0.374 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms10-85, Type 1, Class A Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30NR6K14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.