

## P/N BACB30NT2K4

### **Description**

Fastener Length: 41/64", Thread: 8-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	BACB30N12K4
Minimum Qty (MOQ):	20
NSN:	5305-01-339-1417
Schodula Pr	9109 00 2060

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACB30NT2K4 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.389 Inches Nominal
Fastener Length:	0.624 Inches Minimum And 0.654 Inches Maximum
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
lii Part Name Assigned By Controlling Agency:	Navy Special Project
Color:	Black Threads
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unf

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30NT2K4">https://military-fasteners.com/bolts/machine+bolts/BACB30NT2K4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.