

# P/N BACB30NT3K22

## **Description**

Fastener Length: 1-23/32", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model:	BACB30NT3K22
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-580-9517
Schedule B:	8108.90.3060
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACB30NT3K22 Specifications**

Thread Class:	3a
Thread Direction:	
	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	1.720 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Grip Diameter:	0.1881 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	32
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Bolt, Pan Head, Cross Recess, Short Thread
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms 10-85, Type 1 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30NT3K22">https://military-fasteners.com/bolts/machine+bolts/BACB30NT3K22</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.