

P/N BACB30NT3K3

Description

Fastener Length: 35/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACB30NT3K3

Minimum Qty (MOQ): 20 EA

NSN: 5305-01-254-5401

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



^{*} See page 2 for technical characteristics

P/N BACB30NT3K3 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.320 Inches Minimum And 0.370 Inches Maximum
Fastener Length:	0.518 Inches Minimum And 0.548 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Titanium Alloy Uns R56400
Screw Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response
Screw Surface Treatment:	Aluminum
Screw Surface Treatment Document And Classification:	Bms10-85,cagec81205 National Spec Single Treatment Response
Special Features:	Identify With Black Dye Or Paint On Threaded End
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30NT3K3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.