

**Description**

Fastener Length: 39/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | BACB30NT3K4                          |
| Minimum Qty (MOQ):      | 15 EA                                |
| NSN:                    | 5305-01-209-9377                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | EAR99                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N BACB30NT3K4 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.320 Inches Minimum And 0.370 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.580 Inches Minimum And 0.610 Inches Maximum  |
| <b>Head Style:</b>                                    | Pan  |
| <b>Head Diameter:</b>                                 | 0.357 Inches Minimum And 0.373 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.122 Inches Minimum And 0.133 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 0.240 Inches Minimum And 0.260 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Material:</b>                                      | Titanium Alloy Overall   |
| <b>Material Document And Classification:</b>          | Ams 4967 6al-4v Assn Std Single Material Response Or Ams 4928 6al-4v Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Aluminum Overall   |
| <b>Surface Treatment Document And Classification:</b> | Bms 10-85 Ty 1,fscm 81205 Mfr Ref Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NT3K4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.