

Description

Fastener Length: 39/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | BACB30NT3K4 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-209-9377 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N BACB30NT3K4 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.320 Inches Minimum And 0.370 Inches Maximum |
| Fastener Length: | 0.580 Inches Minimum And 0.610 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4967 6al-4v Assn Std Single Material Response Or Ams 4928 6al-4v Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Bms 10-85 Ty 1,fscm 81205 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NT3K4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.