

P/N BACB30NT4K15

Description

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | BACB30NT4K15 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-580-9528 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |



^{*} See page 2 for technical characteristics

P/N BACB30NT4K15 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.389 Inches Nominal |
| Fastener Length: | 1.327 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.473 Inches Minimum And 0.492 Inches Maximum |
| Head Height: | 0.162 Inches Minimum And 0.175 Inches Maximum |
| Grip Diameter: | 0.2481 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.928 Inches Minimum And 0.948 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Part Name Assigned By Controlling Agency: | Bolt, Pan Head, Cross Recess, Short Thread |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Bms 10-85, Type 1 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30NT4K15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.