

Description

Fastener Length: 1-7/16", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NT4K17
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-580-9525
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N BACB30NT4K17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.389 Inches Nominal
Fastener Length:	1.451 Inches Nominal
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Grip Diameter:	0.2481 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.052 Inches Minimum And 1.072 Inches Maximum
Thread Quantity Per Inch:	28
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Bolt, Pan Head, Cross Recess, Short Thread
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms 10-85, Type 1 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NT4K17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.