

Description

BACB30NW8K10 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NW8K10
Minimum Qty (MOQ):	10
NSN:	5320-01-339-4096
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N BACB30NW8K10 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Fastener Length:	1.010 Inches Minimum And 1.030 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.399 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.620 Inches Minimum And 0.630 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms 10-85,ty 1,cagec 81205 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/BACB30NW8K10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.