

# P/N BACB30NX16K25

## **Description**

Fastener Length: 2-1/4", Thread Size: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30NX16K25

Minimum Qty (MOQ): 1 EA

NSN: 5320-01-337-2022

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N BACB30NX16K25 Specifications

Thread Class:	3a
Thread Direction:	
	Right-hand
Fastener Length:	2.237 Inches Minimum And 2.257 Inches Maximum
Head Style:	Err-090
Head Height:	0.178 Inches Minimum And 0.188 Inches Maximum
Width Between Flats:	0.2207 Inches Minimum And 0.2242 Inches Maximum
Shank Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.717 Inches Minimum And 0.770 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	1.557 Inches Minimum And 1.567 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.500 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Threads Are Color Coded Black
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi Kote 1,cagec 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30NX16K25">https://military-fasteners.com/bolts/machine+bolts/BACB30NX16K25</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.