

Description

Fastener Length: 1-53/64", Thread Size: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NX20K16
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-337-3375
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N BACB30NX20K16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.815 Inches Minimum And 1.835 Inches Maximum
Head Style:	Err-090
Head Height:	0.228 Inches Minimum And 0.238 Inches Maximum
Width Between Flats:	0.2520 Inches Minimum And 0.2555 Inches Maximum
Shank Diameter:	0.6230 Inches Minimum And 0.6240 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.905 Inches Minimum And 0.953 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.995 Inches Minimum And 1.005 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.625 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Threads Are Color Coded Black
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi Kote 1,cagec 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NX20K16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.