

Description

Fastener Length: 1-61/64", Thread Size: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30NY20K18
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-592-8361
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N BACB30NY20K18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.940 Inches Minimum And 1.960 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.252 Nominal Mils And 0.256 Nominal Centimeters
Shank Diameter:	0.623 Inches Minimum And 0.624 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	1.262 Inches Minimum And 1.277 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	1.120 Nominal Mils And 1.130 Nominal Centimeters
Thread Quantity Per Inch:	18
Nominal Thread Size:	0.625 Inches
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NY20K18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.