

**Description**

Fastener Length: 2-41/64", Thread Size: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30NY20K29
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-592-8500
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N BACB30NY20K29 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	2.627 Inches Minimum And 2.647 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.252 Inches Minimum And 0.256 Inches Maximum
<b>Shank Diameter:</b>	0.623 Inches Minimum And 0.624 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	1.262 Inches Minimum And 1.277 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	1.807 Inches Minimum And 1.817 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18
<b>Nominal Thread Size:</b>	0.625 Inches
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NY20K29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.