

Description

BACB30NY8K8 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | BACB30NY8K8 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-178-8680 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACB30NY8K8 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.885 Inches Minimum And 0.905 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.095 Inches Minimum And 0.097 Inches Maximum |
| Shank Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.502 Inches Minimum And 0.507 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.505 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Nominal Thread Size: | 0.250 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | 294,fscm 73197 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/BACB30NY8K8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.