

Description

Fastener Length: 1-3/32", Thread: 1/4-24, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30PN58
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-217-0682
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACB30PN5-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.568 Inches Minimum And 0.618 Inches Maximum
Fastener Length:	1.078 Inches Minimum And 1.108 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.220 Inches Minimum And 0.260 Inches Maximum
Width Between Flats:	0.397 Inches Minimum And 0.413 Inches Maximum
Extended Washer Diameter:	0.575 Inches Minimum And 0.585 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams5662 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30PN5-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.