

**Description**

Fastener Length: 1-3/32", Thread: 1/4-24, Thread Length: 39/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | BACB30PN58                                       |
| Minimum Qty (MOQ):      | 1 EA   |
| NSN:                    | 5306-01-217-0682                                 |
| Schedule B:             | 7508.90.5000                                     |
| ECCN:                   | EAR99  |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE  
AVAILABLE

## P/N BACB30PN5-8 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.568 Inches Minimum And 0.618 Inches Maximum     |
| <b>Fastener Length:</b>                      | 1.078 Inches Minimum And 1.108 Inches Maximum     |
| <b>Head Style:</b>                           | Spline Extended Washer                            |
| <b>Head Height:</b>                          | 0.220 Inches Minimum And 0.260 Inches Maximum     |
| <b>Width Between Flats:</b>                  | 0.397 Inches Minimum And 0.413 Inches Maximum     |
| <b>Extended Washer Diameter:</b>             | 0.575 Inches Minimum And 0.585 Inches Maximum     |
| <b>Extended Washer Thickness:</b>            | 0.040 Inches Minimum And 0.050 Inches Maximum     |
| <b>Grip Diameter:</b>                        | 0.3115 Inches Minimum And 0.3120 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>              | 0.312 Inches                                      |
| <b>Grip Length:</b>                          | 0.490 Inches Minimum And 0.510 Inches Maximum     |
| <b>Thread Quantity Per Inch:</b>             | 24  |
| <b>Minimum Tensile Strength:</b>             | 180000 Pounds Per Square Inch                     |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head          |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                             |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                          |
| <b>Material:</b>                             | Nickel Alloy 718 Overall                          |
| <b>Material Document And Classification:</b> | Ams5662 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30PN5-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.