

Description

Fastener Length: 1-5/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30PU4D17
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-202-7688
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACB30PU4D17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.310 Inches Minimum And 0.360 Inches Maximum
Fastener Length:	1.048 Inches Minimum And 1.078 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Shoulder Diameter:	0.2490 Inches Minimum First Shoulder And 0.2495 Inches Maximum First Shoulder
Shoulder Length:	0.718 Inches Minimum First Shoulder And 0.738 Inches Maximum First Shoulder
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.875 Inches Minimum First Hole And 0.925 Inches Maximum First Hole
Shoulder Shape:	Round First Shoulder
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30PU4D17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.