

**Description**

Fastener Length: 1-5/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACB30PU4D17
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-202-7688
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N BACB30PU4D17 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.310 Inches Minimum And 0.360 Inches Maximum
<b>Fastener Length:</b>	1.048 Inches Minimum And 1.078 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.140 Inches Minimum And 0.172 Inches Maximum
<b>Width Between Flats:</b>	0.430 Inches Minimum And 0.439 Inches Maximum
<b>Shoulder Diameter:</b>	0.2490 Inches Minimum First Shoulder And 0.2495 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.718 Inches Minimum First Shoulder And 0.738 Inches Maximum First Shoulder
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	0.875 Inches Minimum First Hole And 0.925 Inches Maximum First Hole
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30PU4D17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.