

**Description**

Fastener Length: 1-5/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | BACB30PU4D17                              |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-202-7688                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N BACB30PU4D17 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.310 Inches Minimum And 0.360 Inches Maximum                                 |
| <b>Fastener Length:</b>   | 1.048 Inches Minimum And 1.078 Inches Maximum                                 |
| <b>Head Style:</b>  | Hexagon   |
| <b>Head Height:</b>   | 0.140 Inches Minimum And 0.172 Inches Maximum                                 |
| <b>Width Between Flats:</b>   | 0.430 Inches Minimum And 0.439 Inches Maximum                                 |
| <b>Shoulder Diameter:</b>   | 0.2490 Inches Minimum First Shoulder And 0.2495 Inches Maximum First Shoulder |
| <b>Shoulder Length:</b>   | 0.718 Inches Minimum First Shoulder And 0.738 Inches Maximum First Shoulder   |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole           |
| <b>Nominal Thread Diameter:</b>   | 0.190 Inches  |
| <b>Thread Quantity Per Inch:</b>  | 32  |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 0.875 Inches Minimum First Hole And 0.925 Inches Maximum First Hole           |
| <b>Shoulder Shape:</b>  | Round First Shoulder  |
| <b>Material:</b>  | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>                            | Ams 5737 Assn Std Single Material Response Overall                            |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-35 Fed Spec Single Treatment Response Overall                            |
| <b>Thread Series Designator:</b>  | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30PU4D17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.