

## P/N BACB30PU4D18

## **Description**

Fastener Length: 1-15/32", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30PU4D18

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-412-4847

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N BACB30PU4D18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	1.470 Inches Nominal
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Shoulder Diameter:	0.2490 Inches Minimum First Shoulder And 0.2495 Inches Maximum First Shoulder
Shoulder Length:	1.125 Inches Nominal First Shoulder
Shank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.307 Inches Nominal First Hole
Shoulder Shape:	Round First Shoulder
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30PU4D18">https://military-fasteners.com/bolts/machine+bolts/BACB30PU4D18</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.