



Military-Fasteners.com

P/N BACB30RF6P13

Description

Fastener Length: 1-19/64", Thread: 3/8-24, Thread Length: 31/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30RF6P13
Minimum Qty (MOQ):	1
NSN:	5305-01-062-1058
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30RF6P13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.445 Inches Minimum And 0.495 Inches Maximum
Fastener Length:	1.267 Inches Minimum And 1.297 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.510 Inches Minimum And 0.566 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp Xm-13 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30RF6P13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.