

Description

BACB30US5K16 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30US5K16
Minimum Qty (MOQ):	2
NSN:	5306-01-421-5112
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30US5K16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.593 Inches Nominal
Fastener Length:	1.593 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.290 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.580 Inches Nominal
Extended Washer Thickness:	0.050 Inches Nominal
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.000 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams5662 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Mil-c-85614 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/BACB30US5K16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.