

P/N BACB30US5K16

Description

BACB30US5K16 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30US5K16

Minimum Qty (MOQ):

NSN: 5306-01-421-5112

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30US5K16 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.593 Inches Nominal |
| Fastener Length: | 1.593 Inches Nominal |
| Head Style: | Double Hexagon Extended Washer |
| Head Height: | 0.290 Inches Nominal |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Extended Washer Diameter: | 0.580 Inches Nominal |
| Extended Washer Thickness: | 0.050 Inches Nominal |
| Grip Diameter: | 0.311 Inches Minimum And 0.312 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.000 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Mil-c-85614 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/BACB30US5K16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.