

Description

BACB30US5K19 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30US5K19
Minimum Qty (MOQ):	2
NSN:	5306-01-386-9032
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N BACB30US5K19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.593 Inches Nominal
Fastener Length:	1.766 Inches Minimum And 1.796 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.290 Inches Minimum And 0.310 Inches Maximum
Width Between Flats:	0.360 Inches Minimum And 0.375 Inches Maximum
Extended Washer Diameter:	0.575 Inches Minimum And 0.585 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum And 0.060 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material:	Nickel Alloy K-500 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms 10-85 Ty 1 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/BACB30US5K19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.