

P/N BACB30US5K19

Description

BACB30US5K19 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30US5K19

Minimum Qty (MOQ):

NSN: 5306-01-386-9032

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



^{*} See page 2 for technical characteristics

P/N BACB30US5K19 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.593 Inches Nominal |
| Fastener Length: | 1.766 Inches Minimum And 1.796 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.290 Inches Minimum And 0.310 Inches Maximum |
| Width Between Flats: | 0.360 Inches Minimum And 0.375 Inches Maximum |
| Extended Washer Diameter: | 0.575 Inches Minimum And 0.585 Inches Maximum |
| Extended Washer Thickness: | 0.040 Inches Minimum And 0.060 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.178 Inches Minimum And 1.198 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Material: | Nickel Alloy K-500 Overall |
| Material Document And Classification: | Ams 5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Bms 10-85 Ty 1 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/BACB30US5K19 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.