

## P/N BACB30US6K19

### **Description**

BACB30US6K19 Shear Bolt

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30US6K19

Minimum Qty (MOQ):

NSN: 5306-01-338-8149

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N BACB30US6K19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.643 Inches Nominal
Fastener Length:	3.003 Inches Minimum And 3.033 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.330 Inches Minimum And 0.350 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.081 Inches Minimum And 0.101 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.365 Inches Minimum And 2.385 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms10-85,cagec 81205 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/BACB30US6K19">https://military-fasteners.com/bolts/shear+bolts/BACB30US6K19</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.