

Description

BACB30US6K23 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30US6K23
Minimum Qty (MOQ):	1
NSN:	5306-01-109-7465
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACB30US6K23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.618 Inches Minimum And 0.668 Inches Maximum
Fastener Length:	2.066 Inches Minimum And 2.096 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.378 Inches Minimum And 0.398 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.081 Inches Minimum And 0.101 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.428 Inches Minimum And 1.448 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 49.0 Rockwell C Maximum Overall
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/BACB30US6K23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.