

Description

BACB30VF3K3 Close Tolerance Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | BACB30VF3K3 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-01-190-4588 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N BACB30VF3K3 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.308 Inches Minimum And 0.338 Inches Maximum |
| Fastener Length: | 0.501 Inches Minimum And 0.521 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.271 Inches Minimum And 0.303 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.183 Inches Minimum And 0.193 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Special Features: | Black Dye Or Paint On Thread End |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Bms 10-85,type 1,fscm 81205 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/BACB30VF3K3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.