

Description

Fastener Length: 25/64", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30VT5HK2
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-444-3782
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N BACB30VT5HK2 Specifications

Thread Class:	3a
Fastener Length:	0.395 Inches Nominal
Head Style:	Err-090
Head Height:	0.037 Inches Nominal
Width Between Flats:	0.063 Inches Nominal
Shank Diameter:	0.162 Inches Nominal
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Nominal
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.120 Inches Nominal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi-kote 1 Cagec 73197 Mfr Ref Single Treatment Response Overall

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30VT5HK2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.