

P/N BACB30VT6K12

Description

Fastener Length: 1-3/64", Thread Size: 3/16",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACB30VT6K12

Minimum Qty (MOQ): 20

NSN: 5320-01-337-6724

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed







^{*} See page 2 for technical characteristics

P/N BACB30VT6K12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.030 Inches Minimum And 1.050 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.745 Inches Minimum And 0.755 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Color Code Orange On Thread End
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi Kote 1,cagec 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30VT6K12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.