

**Description**

Fastener Length: 47/64", Thread Size: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30VT6K7X
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-438-7136
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N BACB30VT6K7X Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.718 Inches Minimum And 0.738 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.045 Inches Minimum And 0.055 Inches Maximum
<b>Width Between Flats:</b>	0.0781 Inches Minimum And 0.0806 Inches Maximum
<b>Shank Diameter:</b>	0.2641 Inches Minimum And 0.2651 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.295 Inches Minimum And 0.315 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.423 Inches Minimum And 0.443 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Special Features:</b>	Color Code Orange On Thread End
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Surface Treatment Document And Classification:</b>	Hi Hote 1, Cagec 73197 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30VT6K7X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.