

Description

Fastener Length: 47/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | BACB30VT6K7X |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5320-01-438-7136 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N BACB30VT6K7X Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.718 Inches Minimum And 0.738 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.045 Inches Minimum And 0.055 Inches Maximum |
| Width Between Flats: | 0.0781 Inches Minimum And 0.0806 Inches Maximum |
| Shank Diameter: | 0.2641 Inches Minimum And 0.2651 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.295 Inches Minimum And 0.315 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.423 Inches Minimum And 0.443 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Special Features: | Color Code Orange On Thread End |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Hi Hote 1, Cagec 73197 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30VT6K7X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.