

Description

Fastener Length: 1-25/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30VU10K16
Minimum Qty (MOQ):	35 EA
NSN:	5320-01-338-9366
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N BACB30VU10K16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.370 Inches Minimum And 1.390 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.1270 Inches Minimum And 0.1295 Inches Maximum
Shank Diameter:	0.3020 Inches Minimum And 0.3120 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.4689 Inches Minimum And 0.4739 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.995 Inches Minimum And 1.005 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Identify With Color Code Black On Thread End
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi-kote 1,spec. 294,cagec 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30VU10K16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.