

**Description**

Fastener Length: 15/32", Thread Size: 5/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30VU5K3
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-338-6907
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N BACB30VU5K3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.458 Inches Minimum And 0.478 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.0635 Inches Minimum And 0.0645 Inches Maximum
<b>Shank Diameter:</b>	0.1625 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.2564 Inches Minimum And 0.2612 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.183 Inches Minimum And 0.193 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Identify With Color Code Black On Thread End
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Surface Treatment Document And Classification:</b>	Hi0kote 1,spec. 294,cagec 73197 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30VU5K3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.