

P/N BACB30XD3K5

Description

Fastener Length: 41/64", Thread: 10-32, Thread Length: 21/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACB30XD3K5

Minimum Qty (MOQ): 20

NSN: 5305-01-580-9974

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N BACB30XD3K5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.318 Inches Minimum And 0.328 Inches Maximum
Fastener Length:	0.620 Inches Minimum And 0.650 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.322 Inches Nominal
Grip Diameter:	0.1881 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.307 Inches Minimum And 0.317 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Bolt, Pan Head, Cross Recess, Short Thread
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms 10-85, Type 1 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30XD3K5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.