

Description

Fastener Length: 41/64", Thread: 10-32, Thread Length: 21/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | BACB30XD3K5 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-01-580-9974 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N BACB30XD3K5 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.318 Inches Minimum And 0.328 Inches Maximum |
| Fastener Length: | 0.620 Inches Minimum And 0.650 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.322 Inches Nominal |
| Grip Diameter: | 0.1881 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.307 Inches Minimum And 0.317 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 100.0 Degrees Nominal |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Part Name Assigned By Controlling Agency: | Bolt, Pan Head, Cross Recess, Short Thread |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Bms 10-85, Type 1 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30XD3K5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.