

# P/N BACB30XD3K6

### **Description**

BACB30XD3K6 Close Tolerance Screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30XD3K6

Minimum Qty (MOQ): 10

NSN: 5305-01-580-9980

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACB30XD3K6 Specifications**

Thread Class: 3a  Thread Direction: Right-hand  2.310 below Minimum And 0.320 below Minimum	
Three differentials	
Thread Length: 0.318 Inches Minimum And 0.328 Inches Maximum	
Fastener Length: 0.683 Inches Minimum And 0.713 Inches Maximum	
Head Style: Flat Countersunk	
Head Diameter: 0.322 Inches Nominal	
Grip Diameter: 0.1881 Inches Minimum And 0.1895 Inches Maximum	
Internal Drive Style: Cross Recess Type 1	
Nominal Thread Diameter: 0.190 Inches	
Grip Length: 0.370 Inches Minimum And 0.380 Inches Maximum	
Thread Quantity Per Inch: 32	
Countersink Angle: 100.0 Degrees Nominal	
Surface Finish: 32.0 Microinches Bearing Surface Of Head	
Surface Finish: 32.0 Microinches Grip	
Surface Finish: 32.0 Microinches Threads	
Part Name Assigned By Controlling Agency: Bolt, Pan Head, Cross Recess, Short Thread	
Material: Titanium Alloy Overall	
Material Document And Classification: Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 A	all
Surface Treatment: Aluminum Overall	
Surface Treatment Document And Classification: Bms 10-85, Type 1 Assn Std Single Treatment Response Overall	
Thread Series Designator: Unjf	

## **How to Order**

Order this close tolerance screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/BACB30XD3K6">https://military-fasteners.com/screws/close+tolerance+screws/BACB30XD3K6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.