

Description

BACC30BH12 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACC30BH12
Minimum Qty (MOQ):	10
NSN:	5320-01-240-1871
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N BACC30BH12 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.622 Inches Minimum And 0.628 Inches Maximum
Collar Overall Height:	0.720 Inches Minimum And 0.740 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.397 Inches Minimum And 0.403 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 302 Overall Or Steel Comp Xm-7 Overall Or Steel Comp 305 Overall
Material Document And Classification:	Astm A493 Assn Std 1st Material Response Overall Or Astm A493 Assn Std 2nd Material Response Overall Or Qq-s-763 Fed Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/BACC30BH12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.