

Description

BACC30BH12 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACC30BH12 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-240-1871 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N BACC30BH12 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.622 Inches Minimum And 0.628 Inches Maximum |
| Collar Overall Height: | 0.720 Inches Minimum And 0.740 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Collar Inside Diameter: | 0.397 Inches Minimum And 0.403 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.375 Inches |
| Collar Style: | Threaded (break Off) Type |
| Material: | Steel Comp 302 Overall Or Steel Comp Xm-7 Overall Or Steel Comp 305 Overall |
| Material Document And Classification: | Astm A493 Assn Std 1st Material Response Overall Or Astm A493 Assn Std 2nd Material Response Overall Or Qq-s-763 Fed Spec 3rd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-riev collar from our inventory online by visiting https://military-fasteners.com/collars/pin_riev+collars/BACC30BH12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.