

Description

BACC30R6 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACC30R6
Minimum Qty (MOQ):	25
NSN:	5320-00-457-1332
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N BACC30R6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Blue
Collar Outside Diameter:	0.325 Inches Minimum And 0.335 Inches Maximum
Collar Overall Height:	0.437 Inches Minimum And 0.457 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.223 Inches Minimum And 0.227 Inches Maximum
Nominal Thread Size:	0.190 Inches
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-riev collar from our inventory online by visiting https://military-fasteners.com/collars/pin_riev+collars/BACC30R6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.