

Description

Thread Size: 3/4", Nut Height: 1", Nut Length: 1-7/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACN10HC12
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-145-0813
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACN10HC12 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.781 Inches Minimum Nut And 0.791 Inches Maximum Nut
Lubrication:	Dry Film Lubricant
Nut Style:	Non-floating Self-locking Barrel
Nut Diameter:	1.2375 Inches Minimum And 1.2405 Inches Maximum
Nut Length:	1.209 Inches Minimum And 1.229 Inches Maximum
Barrel Height:	0.729 Inches Minimum And 0.749 Inches Maximum
Nut Height:	0.982 Inches Maximum
Nut Counterbore Depth:	0.190 Inches Minimum Nut And 0.210 Inches Maximum Nut
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	16
Nominal Thread Size:	0.750 Inches
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/clip_on+nuts/BACN10HC12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.