

Description

Thread Size: 3/8", Nut Length: 5/8", Nut Height: 1/2

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACN10HC6
Minimum Qty (MOQ):	2
NSN:	5310-01-033-2676
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACN10HC6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.406 Inches Minimum Nut And 0.416 Inches Maximum Nut
Lubrication:	Dry Film Lubricant Or Soluble Lubricant
Nut Style:	Non-floating Self-locking Barrel
Nut Diameter:	0.646 Inches Minimum And 0.656 Inches Maximum
Nut Length:	0.646 Inches Minimum And 0.666 Inches Maximum
Barrel Height:	0.391 Inches Minimum And 0.411 Inches Maximum
Nut Height:	0.556 Inches Maximum
Nut Counterbore Depth:	0.140 Inches Minimum Nut And 0.160 Inches Maximum Nut
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Hardness Rating:	43.0 Rockwell C Maximum
Nominal Thread Size:	0.375 Inches
Special Features:	Color Blue
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	Ams 6322 Assn Std 1st Material Response Overall Or Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	81205-bacn10hc Manufacturers Standard

How to Order

Order this self-locking barrel nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+barrel+nuts/BACN10HC6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.