

## P/N BACN10HC8A

## **Description**

Thread Size: 1/2", Nut Length: 7/8", Nut Height: 3/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACN10HC8A

Minimum Qty (MOQ): 5 EA

NSN: 5310-01-058-7088

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACN10HC8A Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.531 Inches Minimum Nut And 0.541 Inches Maximum Nut
Lubrication:	Soluble Lubricant
Nut Style:	Floating Self-locking Barrel
Nut Diameter:	0.848 Inches Minimum And 0.858 Inches Maximum
Nut Length:	0.859 Inches Nominal
Barrel Height:	0.541 Inches Minimum And 0.561 Inches Maximum
Nut Height:	0.715 Inches Maximum
Nut Counterbore Depth:	0.190 Inches Minimum Nut And 0.210 Inches Maximum Nut
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	20
Hardness Rating:	43.0 Rockwell C Maximum
Nominal Thread Size:	0.500 Inches
Special Features:	Color Identification Blue
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	81205-bacn10hc Manufacturers Standard

## **How to Order**

Order this locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/clip\_on+nuts/BACN10HC8A">https://military-fasteners.com/nuts/clip\_on+nuts/BACN10HC8A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.