

P/N BACN10JN04

Military-Fasteners.com

Description

Thread Size: 1/4", Nut Length: 1-9/32", Nut Height: 9/32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	BACN10JN04	
Minimum Qty (MOQ):	5	
NSN:	5310-00-777-5793	
Schedule B:	7318.16.0085	
ECCN:	9A991	
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)	



P/N BACN10JN04 Specifications

Thread Class:3bThread Direction:Night-AndLocking Feature:Prevailing Torque All Metal DesignLubrication:Dy Finu LubricantMounting Hole Diameter:0.098 Inches Maximum And 0.103 Inches MaximumNut Style:PateNut Length:0.292 Inches MaximumNut Height:0.203 Inches MaximumPlate Michanes0.032 Inches MaximumNut Height:0.350 Inches MaximumPlate Michanes0.032 Inches MaximumPlate Michanes0.032 Inches MaximumNut Height:0.032 Inches MaximumNut Height:0.032 Inches MaximumNut Height:0.035 Inches MaximumNut Height:0.035 Inches MaximumNut Height:0.998 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Hole Center:0.998 Inches Minimum And 1.002 Inches MaximumThread Series:0.1045 Inches MaximumFeatures Provided:Floating NutThread Quarity Per Inch:2Nateries:0.030 Inches MaximumNominal Thread Size:0.205 InchesNateries:0.205 InchesNateries:0.205 InchesNateries:0.205 InchesNateries:0.205 InchesNateries:0.205 InchesNateries:0.205 Inches<		
Locking Feature:Prevailing Torque All Metal DesignLubrication:Dry Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:1.292 Inches MaximumNut Height:0.032 Inches MaximumPlate Mitcheres:0.032 Inches MaximumPlate Mitcheres:0.032 Inches MaximumPlate Width:0.350 Inches Minimum And 0.516 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter Distance Between Mounting Hole Salong Length:0.998 Inches Minimum And 0.505 Inches MaximumThread Series:UnifFeatures Provided:Floating NutThread Sating:0.400 Rockwell C MaximumNominal Thread Size:0.250 InchesMounting Hore Inche:0.250 InchesStarling:1.002 Rockwell C MaximumThread Sating:0.400 Rockwell C MaximumMonter Intrace Size:0.250 InchesMaterial:0.250 InchesMaterial:Steel Overall	Thread Class:	3b
Lubrication:Dry Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:1.292 Inches MaximumNut Length:0.281 Inches MaximumPlate0.281 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.350 Inches Minimu And 0.516 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 0.102 Inches MaximumTimp Rating:100 Epairenheit NominalThread Series:UnjfFeatures Provided:8Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMominal Thread Size:0.250 InchesMominal Thread Size:0.250 InchesMominal Thread Size:0.250 InchesMaterial:Steel Overall	Thread Direction:	Right-hand
Mounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:1.292 Inches MaximumNut Height:0.281 Inches MaximumPlate0.322 Inches MaximumPlate Thickness:0.322 Inches MaximumPlate Width:0.350 Inches Minimum And 0.516 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Holes Along Length:0.998 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTheng Saries:0.998 Inches Minimum And 1.002 Inches MaximumThread Series:10.998 Inches Minimum And 1.002 Inches MaximumThread Saries:9.998 Inches Minimum And 1.002 Inches MaximumThread Saries:9.000 InchesMarting:9.000 InchesMarting:82Marting:9.000 InchesMarting:9.000 InchesMarting:9.000 InchesMarting:9.000 InchesMarting:9.000 InchesMarting:9.000 InchesMarting:9.000 InchesMarting:9.000 InchesMarting:9.000 InchesMarting:9.	Locking Feature:	Prevailing Torque All Metal Design
Nut Style:PlateNut Length:1.292 Inches MaximumNut Height:0.281 Inches MaximumPlate Thickness:0.322 Inches MaximumPlate Thickness:0.332 Inches MaximumPlate Width:0.350 Inches Minimum And 0.516 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:Valore Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread State:0.250 InchesNominal Thread Size:0.250 InchesNominal Thread Size:0.250 InchesMounting Holes Inches0.250 InchesSurface Treatment:Steel Overall	Lubrication:	Dry Film Lubricant
Nut Length:1.292 Inches MaximumNut Height:0.281 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.350 Inches Minimum And 0.516 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Along Length:0.998 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Hardness Rating:0.250 InchesNominal Thread Size:0.250 InchesMaterial:0.250 InchesSurface Treatment:Cadmium Overall	Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Height:0.281 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.350 Inches Minimum And 0.516 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Hole Along Length:0.998 Inches Minimum And 0.505 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Reatures Provided:Thread Quantity Per Inch:28Hardness Rating:0.250 InchesNominal Thread Size:0.250 InchesMaterial:Steel Overall	Nut Style:	Plate
Plate Trickness:0.032 Inches MaximumPlate Width:0.350 Inches Minimum And 0.516 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 0.002 Inches MaximumTemp Rating:0.998 Inches Minimum And 1.002 Inches MaximumThread Series:UnifFeatures Provided:Foating NutThread Quantity Per Inch:28Hardness Rating:0.250 InchesNominal Thread Size:0.250 InchesMominal Thread Size:0.250 InchesMaterial:Stel OverallSurface Treatment:Cadmium Overall	Nut Length:	1.292 Inches Maximum
Plate Width:0.350 Inches Minimum And 0.516 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 0.502 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Hardness Rating:0.250 InchesNominal Thread Size:0.250 InchesMominal Thread Size:0.250 InchesMaterial:Steel Overall	Nut Height:	0.281 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Hardness Rating:0.250 InchesNominal Thread Size:0.250 InchesMaterial:Steel OverallSurface Treatment:Cadmium Overall	Plate Thickness:	0.032 Inches Maximum
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Hardness Rating:0.908 Nockwell C MaximumNominal Thread Size:0.250 InchesMountinal Thread Size:0.250 InchesSurface Treatment:Cadmium Overall	Plate Width:	0.350 Inches Minimum And 0.516 Inches Maximum
Distance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Hardness Rating:0.490 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Steel OverallSurface Treatment:Cadmium Overall	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Steel OverallSurface Treatment:Cadmium Overall	Mounting Hole Arrangement Style:	2 Holes
Temp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Steel OverallSurface Treatment:Cadmium Overall	Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Thread Series:UnjfFeatures Provided:Foating NutThread Quantity Per Inch:SaHardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Steel OverallSurface Treatment:Cadmium Overall	Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Features Provided:Floating NutFread Quantity Per Inch:SaHardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Steel OverallSurface Treatment:Cadmium Overall	Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Steel OverallSurface Treatment:Cadmium Overall	Thread Series:	Unjf
Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Steel OverallSurface Treatment:Cadmium Overall	Features Provided:	Floating Nut
Nominal Thread Size: 0.250 Inches Material: Steel Overall Surface Treatment: Cadmium Overall	Thread Quantity Per Inch:	28
Material: Steel Overall Surface Treatment: Cadmium Overall	Hardness Rating:	49.0 Rockwell C Maximum
Surface Treatment: Cadmium Overall	Nominal Thread Size:	0.250 Inches
	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+nutplates/BACN10JN04</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.