

P/N BACN10JN3CM

Description

Thread Size: 3/16", Nut Length: 47/64", Nut Height: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACN10JN3CM
Minimum Qty (MOQ):	15 EA
NSN:	5310-01-030-4907
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



^{*} See page 2 for technical characteristics

P/N BACN10JN3CM Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.739 Inches Maximum
Nut Height:	0.390 Inches Maximum
Plate Width:	0.416 Inches Maximum
Nut Counterbore Depth:	0.060 Inches Nominal Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.245 Inches Minimum And 0.255 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.498 Inches Minimum And 0.502 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	81205-bacn10jn Manufacturers Standard

How to Order

Order this plate - two lug locknut from our inventory online by visiting https://military-fasteners.com/nuts/clip_on+nuts/BACN10JN3CM and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.