

# P/N BACN10JP3ACD

## **Description**

Thread Size: 3/16", Nut Length: 23/32", Nut Height: 1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: BACN10JP3ACD

Minimum Qty (MOQ): 20 EA

NSN: 5310-01-339-0940

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

## P/N BACN10JP3ACD Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.724 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.328 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.245 Inches Minimum And 0.255 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.498 Inches Minimum And 0.502 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.1900 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	81205-bacn10jp Manufacturers Standard

### **How to Order**

Order this locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/clip\_on+nuts/BACN10JP3ACD">https://military-fasteners.com/nuts/clip\_on+nuts/BACN10JP3ACD</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.