

Description

Thread Size: 3/16", Nut Length: 1/2", Nut Height: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACN10JP3CCM
Minimum Qty (MOQ):	15 EA
NSN:	5310-01-039-6643
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N BACN10JP3CCM Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Nominal Mils And 0.103 Nominal Centimeters
Nut Style:	Plate
Nut Length:	0.526 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Nominal Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.245 Inches Minimum And 0.255 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/clip_on+nuts/BACN10JP3CCM and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.