

**Description**

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | BACN10JR3R                                |
| Minimum Qty (MOQ):      | 50 EA                                     |
| NSN:                    | 5310-01-077-1017                          |
| Schedule B:             | 9401.90.5081                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

# P/N BACN10JR3R Specifications

|  |   |
|--|---|
| Thread Class:  | 3b  |
| Thread Direction:  | Right-hand  |
| Locking Feature:   | Prevailing Torque All Metal Design  |
| Counterbore Diameter:  | 0.194 Inches Minimum Nut  |
| Lubrication:   | Dry Film Lubricant  |
| Mounting Hole Diameter:  | 0.098 Inches Minimum And 0.103 Inches Maximum   |
| Nut Style:   | Plate   |
| Nut Length:  | 0.948 Inches Maximum  |
| Nut Height:  | 0.250 Inches Maximum  |
| Plate Thickness:   | 0.047 Inches Maximum  |
| Plate Width:   | 0.328 Inches Maximum  |
| Nut Counterbore Depth:   | 0.060 Inches Nominal Nut  |
| Nut Mounting Provision:  | Countersunk Holes   |
| Mounting Provision Location:                                   | Opposite Nut Projection Side  |
| Mounting Hole Arrangement Style:                               | 2 Holes   |
| Distance From Aperture Center To Mounting Hole Center:         | 0.339 Inches Minimum And 0.349 Inches Maximum   |
| Center To Center Distance Between Mounting Holes Along Length: | 0.686 Inches Minimum And 0.690 Inches Maximum   |
| Temp Rating:   | 450.0 Deg Fahrenheit Nominal  |
| Thread Series:   | Unjf  |
| Thread Quantity Per Inch:                                      | 32  |
| Nominal Thread Size:   | 0.190 Inches  |
| Mounting Hole Countersink Angle:                               | 98.0 Degrees Minimum And 102.0 Degrees Maximum  |
| Material:  | Steel Comp 1030 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall Or Steel Comp 1038 Overall Or Steel Comp 1039 Overall Or Steel Comp 1040 Overall Or Steel Comp 1541 Overall Or Steel Comp 1045 Overall Or Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1065 Overall Or Steel Comp 1566 Overall Or Steel Comp 1069 Overall Or Steel Comp 1070 Overall |
| Material Document And Classification:                          | 66 Fed Std All Material Responses Overall   |
| Surface Treatment:   | Cadmium Overall   |

|  |  |
|--|--|
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Specification/standard Data:                   | 81205-bacn10jr Manufacturers Standard                              |

## How to Order

Order this plate - two lug locknut from our inventory online by visiting [https://military-fasteners.com/nuts/clip\\_on+nuts/BACN10JR3R](https://military-fasteners.com/nuts/clip_on+nuts/BACN10JR3R) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.